

Gate Max Canada www.gatemax.ca 1 800-561-0656 sales@gatemax.ca

Gate Max Canada 10 Million Cycles Automatic Barrier Boom Gate and 20ft Arms

MAX-10-MILL Barrier Overview

This Automatic Barrier Gate provides a secure and convenient solution of stopping unauthorized vehicle or giving access to authorized vehicle, for parking lots with high traffic flow such as toll gate, shopping mall, exhibition center, hospitals, airport etc.




Description

- Opening/closing time: 0.9~6 sec. adjustable
 Max. 6m straight arm Max. 5m folding arm

- Max. 5.m fence arm Max. 4.5m fence arm 3) Inclusive of <u>arm</u>, <u>2 remoters</u>, and "<u>push button</u>" 4) Exclusive of <u>LED light bar</u>, <u>boom bracket</u> and <u>swing-off</u>: need to buy extra 5) Optional housing color: yellow or customized 6) Easily change boom type (straight/crank/fence) without replacing any parts 2) Dependence of the straight/crank/fence) without replacing any parts

- 7) Boom direction is exchangeable without replacing any parts 8) Price shown in this product for model MAX-10-MILL Barrier only

Straight Arm Barrier




Model No.	Open/Close Time	Max. Boom Length	Boom Type
MAX-10-MILL Barrier - HSN	0.9s	3m	Straight Boom with rubber bar (Octagonal or round)
MAX-10-MILL Barrier - NSN	2s	4m	Straight Boom with rubber bar (Octagonal)
	3s	5m	
	4s	6m	
MAX-10-MILL Barrier - HCN	1s	3.5m	Crank Boom with rubber bar (Octagonal or round)
MAX-10-MILL Barrier - NCN	2~3s	4m	Crank Boom with rubber bar (Octagonal)
	4~s	5m	
MAX-10-MILL Barrier - HFN	2.5~3s	3m	Single Fence Boom
MAX-10-MILL Barrier - NFN	4~6s	4.5m	
MAX-10-MILL Barrier - NFN2	4~6s	4	Double Fence Boom

Features

- 1. Control barrier by smartphone (Optional)
- 2. TCP/IP port for easy integration (Optional)
- 3. Maintenance-free DC brushless motor with 10 million cycles MTBF & 100% duty cycle
- 4. 0.9~6 sec. speed adjustable on controller or APP (Optional)
- 5. Manually control barrier when power is off
- 5. Automatically check status & report errors
- 6. Boom automatically reverses on obstacle
- 7. Boom swing-off protects boom & vehicle
- 8. Alarm when boom swing-off (Optional) 9. Boom direction Is exchangeable without replacing any parts
- 10. Different types of boom can be changed without replacing any parts
- Backup Solar Panel or Lead-acid Cell provides you continuous power supply
 Variable frequency controller automatically detects and optimizes boom moving, ensures smooth moving without shake
- 13. Boom automatically open up fully in case of power failure (Optional)
- Boom valid be automatically locked in case of power failure (Can not work together with function 13 at the same time)
 Safety for Vehicle--- Anti-hit by Loop Detector (Optional)
- 16. Safety for Vehicle--- Anti-hit by IR photocell (Optional)

- Safety for Vehicle--- Anti-hit by "Opening Priority"
 Automatically close in given time (Programmable)
 Automatically close or open by loop detector (Optional)
 Disable/enable function of "Always-open Mode of remoter" on controller
- 21. Disable/enable function of "Memory of Repeated Opening"
- 22. Anti-condensation in cold climate
- 23. Simplified design, easy installation and maintenance reduces your labor cost



MAX-10-MILL Barrier Simplified Design with phone App

Specifications

Opening/closing time	0.9~6s adjustable		
Octagonal Arm	Max. 6mtr 45×100mm aluminum alloy octagonal boom		
	Max. 3m round boom with foam		
Power Supply	AC 85~264V,50/60HZ		
Motor	50W DC24V brushless torque motor		
Duty Cycle	100%		
МТВБ	10 Million Cycles		
Controller	80C51 MCU, 20MHz, PWM variable frequency servo controller board		
Remote distance	20~50mtr.		
Communicatio	n		
	RS-485 or TCP/IP RJ45		
Interface			
Housing material	2mm cold-roller sheet		
Housing Painting	Power coating, 10 years without rust, shedding and fading		
IP level	IP 54		
Housing size	950mm×320mm×329mm		
Package size	1100mm×480mm×430mm		
G.W	46 KG		
Operating temperature	-25°c -55°c		
Humidity	10%-95%		

Contact us for Catalogue and pricelist of MAX-10-MILL Barrier covers all models with different boom shape(straight/crank/fence), boom length(Max.6m) and opening/closing time (0.3~6 sec.).

Gate Max Canada www.gatemax.ca 1 800-561-0656 sales@gatemax.ca